

**Matrix Vapor Deposition System** 

# iMLayer







# ■ Three Features of iMLayer

- Creation of finer matrix crystal grains via the deposition method
- Improved reproducibility of matrix coatings via automatic coating thickness control
- Simple touch panel operation



Spraying







*m/z* 772.52 PC (16.0/16.0) +K

Arrow: cerebellar white matter

Achieves improved resolution and a matrix coating uniformity impossible using the spray method.





After system startup, press (1) and then (2) to start deposition.



Coating thickness measurement area

Sample holder

Matrix boat/heater


Interior of the system

## Specifications

Item	
Applicable matrix*1	DHB, 9-AA, CHCA
Vacuum level attained	1×10 <sup>-2</sup> Pa
Max. temperature	250°C
Sample	one glass slide

Note: This system applies matrix coatings via vacuum deposition. It cannot be used for pretreatment of highly volatile samples. Liquid matrices or highly volatile matrices cannot be used. Use transparent glass slides to control the system by checking the transmitted laser light.

#### Installation Example



Please prepare for the draft chamber at the inside dimension of more than D650 × W1000 × H60 (mm).

Sirrocco fan: CES-V

### Size and Weight

Component (No.)	Size (mm)			Weight (kg)
	W	Н	D	
(a) Main unit	416	610	450	80
(b) Power supply	296	230	390	28
(c) Rotary pump	430	230	163	30

#### Utilities

Power	AC 100V, 50/60Hz, 15A
Max. power consumption	700VA
Current	30 A or more (15 A of this: in the fume hood)
Temp. and humidity	18 °C to 28 °C / 40 % to 70 %

#### Control mode

Coating thickness measurement mode	Set the type of matrix and coating thickness by deposition for automatic operation
Deposition time control mode	Set the type of matrix and deposition time for automatic operation.
Manual adjustment mode	Adjust the deposition time manually while checking the intensity of the transmitted laser light.

<sup>\*</sup>¹ Contact your Shimadzu representative regarding other matrices. Matrix coating is performed via vacuum deposition. Liquid matrices or highly volatile matrices cannot be used.

iMScope TRIO may not be sold in your country. Please contact us to check the availability of iMScope TRIO in your country.



Company names, product/service names and logos used in this publication are trademarks and trade names of Shirmadzu Corporation or its affiliates, whether or not they are used with trademark symbol "TM" or "®".

Third-party trademarks and trade names may be used in this publication to refer to either the entities or their products/services. Shirmadzu disclaims any proprietary interest in trademarks and trade names other than its own.

For Research Use Only. Not for use in diagnostic procedures.
The contents of this publication are provided to you "as is" without warranty of any kind, and are subject to change without notice. Shimadzu does not assume any responsibility or liability for any damage, whether direct or indirect, relating to the use of this publication.